



Dew point sensor FA 510/515 from -80 to 20° Ctd

FA 510/515 - the new generation of dew point sensors for residual moisture measurement in compressed air and gases

Typical applications:

- Dew point measurement in the compressed air after desiccant driers/membrane driers
- Residual moisture/ dew point measurement in gases like oxygen, nitrogen, argon ...
- Residual moisture/ dew point measurement after granulate driers in plastics industry



Recommendation:

Mounting with standard measuring chamber for compressed air up to 16 bar
Advantage: Easy installation via quick coupling



Special features:

- Measuring range -80...20°Ctd
- Extremely long-term stable
- Analogue output 4...20 mA
- Condensation insensitive
- Quick response time
- Pressure-tight up to 350 bar (special version)
- **NEW:** Modbus-RTU interface
- **NEW:** Higher resolution of the sensor signal due to improved evaluation electronics
- **NEW:** Sensor diagnosis on site by means of hand-held instrument or CS Service Software

Technical data

FA 510/515

Measuring range:	-80...20°Ctd
Accuracy:	± 1°C at 20...-20°Ctd ± 2°C at -20...-50°Ctd ± 3°C at -50...-80°Ctd
Pressure range:	-1...50 bar special version up to 350 bar
Power supply:	24 VDC (16...30 VDC)
Protection class:	IP 65
EMV:	according to DIN EN 61326
Operating temp.:	-20...70 °C
Connection:	M12, 5-pole
PC connection:	Modbus-RTU interface (RS 485)
Analogue output:	4...20 mA = -80...20°Ctd FA 510: 4...20 mA (3-wire) FA 515: 4...20 mA (2-wire)
Burden for analogue output:	< 500 Ω
Screw-in thread:	G 1/2" optional: UNF 5/8" NPT 1/2"
Dimensions:	Ø 30 mm, length approx. 130 mm
Via service software:	
Choose units:	% RH, °Ctd, g/m ³ , mg/m ³ , ppm V/V
Scaling:	change 4...20 mA

Description	Order No.
FA 510 dew point sensor for desiccant driers -80...20°Ctd incl. inspection certificate, 4...20 mA output signal (3-wire connection) and Modbus-RTU interface	0699 0510
FA 515 dew point sensor for desiccant driers -80...20°Ctd incl. inspection certificate, 4...20 mA output signal (2-wire connection) or Modbus-RTU interface	0699 0515
Connection cables:	
Connection cable for VA/FA sensors, 5 m	0553 0104
Connection cable for VA/FA sensors, 10 m	0553 0105
Options for FA 510:	
Option analogue output FA510, Special version 2...20 Volt	Z699 0510
Options for FA 510/515:	
Option max. pressure FA5xx 350 bar	Z699 0515
Option max. pressure FA5xx 500 bar	Z699 0516
Option special scaling FA5xx 4...20 mA=___ ... __ g/m ³ , ppm etc.	Z699 0514
Option connection thread FA5xx, 5/8" UNF	Z699 0511
Option connection thread FA5xx, 1/2" NPT	Z699 0512
Option surface condition FA5xx, free of oil & grease	Z699 0517
Additional accessories:	
Standard measuring chamber up to 16 bar	0699 3390
High pressure measuring chamber up to 350 bar	0699 3590
Measuring chamber for respiratory air bottles up to 350 bar	0699 3790
Measuring chamber, stainless steel 1.4305	0699 3290
CS Service Software for dew point sensors incl. PC connection set (Modbus to USB Interface)	0554 2007
Mains unit in wall housing 100-240 V, 10 VA, 50-60 Hz/24 VDC, 0.35 A	0554 0108
Transformer 100-240 V AC/24 V DC , 0,35 A on top-hat rail	0699 3340
Calibration and adjustment:	
Precision calibration at -40°Ctd or 3° Ctd including ISO certificate	0699 3396
Precision calibration in the range of -80 to 20° Ctd, one additional point, freely selectable	0700 7710



Dew point set DS 52 for desiccant driers

Consisting of:

- Digital process meter DS 52 (0500 0009)



- Standard measuring chamber



- Option alarm unit
(buzzer and continuous red light)
(Z500 0003)

- Dew point sensor FA 510 (0699 0510)

The measuring range of $-80...20^{\circ}\text{Ctd}$ makes the dew point set DS 52 with alarm the ideal dew point monitor with analogue output $4...20\text{ mA}$.

The dew point sensor FA 510 is extremely long-term stable and can be installed and removed quickly and easily under pressure by means of the screwable measuring chamber including quick coupling. The dew point set is supplied ready for plug-in, i.e. everything is completely wired. The alarm values can be freely adjusted.

Special features:

- System ready for plug-in: Everything completely wired
- No time-consuming studying of the instruction manual
- 2 alarm contacts (230 VAC, 3 A) pre- and main alarm freely adjustable
- $4...20\text{ mA}$ analogue output
- Option alarm unit: Buzzer and continuous red light

Technical data display DS 52:

Dimensions:	118 x 92 x 93 mm
Display:	LED red, 7 segments, height: 13 mm, 5 digits, 2 LED for alarm relay
Keypad:	4 keys
Input:	$4...20\text{ mA}$
Power supply:	230 VAC, 50/60 Hz; Option: 24 VDC or 110 VAC 50/60 Hz
Alarm outputs:	2 x relay output, changeover contact, 250 VAC, max. 3 A
Operating temperature:	$-10...+60^{\circ}\text{C}$ (storage temp. $-20^{\circ}\text{C}...+80^{\circ}\text{C}$)
Alarm thresholds:	freely adjustable
Hysteresis:	2°Ctd
Analogue output:	$4...20\text{ mA} = -80...20^{\circ}\text{Ctd}$

Technical data dew point sensor FA 510

Measuring range:	$-80...20^{\circ}\text{Ctd}$
Accuracy:	$\pm 1^{\circ}\text{C}$ bei $20...-20^{\circ}\text{Ctd}$ $\pm 2^{\circ}\text{C}$ bei $-20...-50^{\circ}\text{Ctd}$ $\pm 3^{\circ}\text{C}$ bei $-50...-80^{\circ}\text{Ctd}$
Pressure range:	$-1...50\text{ bar}$ special version up to 350 bar
Protection class:	IP 65
EMV:	according DIN EN 61326
Operating temp.:	$-20...70^{\circ}\text{C}$
Connection:	M12, 5-pole
PC connection:	Modbus-RTU interface (RS 485)
Burden for analogue output:	$< 500\ \Omega$
Screw-in thread:	G 1/2"

Description	Order No.
Dew point set DS 52 for desiccant driers consisting of:	0600 5100
DS 52 LED display in wall housing	0500 0009
FA 510 dew point sensor for desiccant driers $-80...20^{\circ}\text{Ctd}$ incl. inspection certificate, $4...20\text{ mA}$ output signal (3-wire connection) and Modbus-RTU interface	0699 0510
Standard measuring chamber up to 16 bar	0699 3390
Connection cable for VA/FA sensors, 5 m	0553 0104
Options:	
Power supply 24 VDC (instead of 230 VAC)	Z500 0001
Power supply 110 VAC (instead of 230 VAC)	Z500 0002
Alarm unit mounted at wall housing	Z500 0003
Alarm unit for external mounting with 5 m cable	Z500 0004
Additional accessories:	
Precision calibration at -40°Ctd including ISO certificate	0699 3396
Precision calibration in the range of -80 to 20°Ctd , one additional point, freely selectable	0700 7710